



Adaptadores de Martillos

Figura Nº	Martillo	Salida de Barrido	D=W	Rosca	Longitud mm	Peso Aproximado	
		mm	mm			Kg	lb
S201	Furukawa PD200/M120/HD200 Gardner Denver PR123/133/55 Ingersoll Rand URD475/550,VL120/140 Mitsui TR300/350S/400 Tamrock L600/750 Toyo PR120/220	14.3	44.1	R32	330	3.3	7.26
		14.3	44.1	R38	349	3.3	7.26
S202	Furukawa PD200/M120/HD200 Gardner Denver PR123/133/55 Ingersoll Rand URD475/550,VL120/140 Mitsui TR300/350S/400 Tamrock L600/750 Toyo PR120/220	14.3	44.3	R38	380	3.7	8.14
		14.3	44.3	T38	380	3.7	8.14
		14.3	44.3	T38	446	4.5	9.90
		14.3	44.3	T45	380	4.1	9.02
		14.3	44.3	T45	446	4.8	10.56
S203	Furukawa PD200R	14.3	44.3	T38	380	4.2	9.24
		14.3	44.3	T38	485	4.8	10.56
		14.3	44.3	T45	485	4.8	10.56
S204	Furukawa HD50	SF	40.0	R38	525	4.3	9.46
		SF	40.0	T38	525	4.3	9.46
S205	Furukawa HD90	SF	40.0	R38	500	4.9	10.80
		SF	40.0	T38	500	4.9	10.80
S206	Furukawa HD135/135A	SF	40.0	R38	501	5.3	11.66





Adaptadores de Martillos

Figura Nº	Martillo	Salida de Barrido	D=W	Rosca	Longitud	Peso Aproximado	
						mm	mm
S207	Furukawa HD150	SF	40.0	R38	520	5.7	12.54
		SF	40.0	T38	520	5.7	12.54
S208	Furukawa HD180	14.3	39.9	T38	565	4.5	9.90
		14.3	39.9	T45	565	4.5	9.90
S209	Furukawa HD210	SF	40.0	T38	410	4.0	8.80
S210	Furukawa HD300	16.0	45.0	T38	655	6.2	13.64
		16.0	45.0	T45	655	6.5	14.30
S211	DNS DNT3 Furukawa HD500 Mitsui DCH400/600 Soosan SP3	16.0	56.0	R38	635	8.0	17.60
		16.0	56.0	T38	620	8.0	17.60
		16.0	56.0	T38	635	8.0	17.60
		16.0	56.0	T45	620	8.0	17.60
		16.0	56.0	T45	635	8.3	18.26
		16.0	56.0	T51	635	8.8	19.36
S212	Soosan SP3	SF	55.8	T45	640	8.3	18.26

